



G-T® RING

Sealing Solutions for Demanding Environments

HIGH-PRESSURE, HIGH-TEMPERATURE SEALS

The unique G-T® Ring provides a compact, double-acting seal for use in new designs or existing applications where O-rings are failing. The G-T Ring can be retrofitted into standard grooves designed for O-rings with one, two or no backups. This proven seal combines a tough, resilient, T-shaped ring with precisely dimensioned, pressure-actuated, anti-extrusion rings for use with pressure ratings in excess of 40,000 psi. For higher pressures consult Greene, Tweed.

FEATURES

- Easy installation
- Excellent resistance to extrusion
- Extended service life
- Unique configuration eliminates seal roll and spiral failure
- Low pressure sealing

The G-T Ring is a static or dynamic seal in “rod” or “piston” configurations for demanding oilfield applications, e.g., cylinders, jacks, intensifiers, tensioners, BOPs, logging equipment, jars, shock subs, bumper subs, pumps, valves and well head equipment.



G-T® ring / product data

Contact Us

Greene, Tweed	Tel: +1.281.765.4500
Energy	Tel: +1.800.927.3301
1930 Rankin Road	Fax: +1.281.821.2696
Houston, TX, USA	

Statements and recommendations in this publication are based on our experience and knowledge of typical applications of this product and shall not constitute a guarantee of performance nor a modification or alteration of our standard warranty which shall be applicable to such products.

© 2016, Greene, Tweed all rights reserved
All trademarks are property of their respective owners.
EN-DS027-US-08-16-2016