



# Chemraz® 600 Sealing Solutions

Compound No./Material Name: <b>Chemraz® 600</b>	Rubber Classification: (ASTM D1418): <b>FFKM</b>	Service Temperature Range: <b>-4°F to 500°F (-20°C to 260°C)</b>	Color: <b>Black</b>
--	---	---	------------------------

Description	Typical
<b>Original Properties (ASTM Standard)</b>	
Specific Gravity (D297)	1.97
Hardness, Shore A Points (D2240)	90
Tensile Strength, psi [MPa] (D1414)	3,250 [22.4]
Elongation, % (D1414)	110
Modulus @ 50% Elongation, psi [MPa] (D1414)	1,410 [9.7]
Modulus @ 100% Elongation, psi [MPa] (D1414)	3,010 [20.8]

*Note*  
Unless otherwise noted, all tests performed on 214 o-rings.

**Contact Us**

Greene Tweed  
Houston, TX, USA

Tel: +1.281.765.4500  
Fax: +1.281.821.2696

Statements and recommendations in this publication are based on our experience and knowledge of typical applications of this product and shall not constitute a guarantee of performance nor modify or alter our standard warranty applicable to such products.  
© 2018, Greene Tweed all rights reserved. All trademarks are property of their respective owners.

08/18-GT DS-US-GE-153