

# Arlon® 1330

## PTFE-Lubricated, Polyketone-Based, High-Performance Components

### **Plastic Components**

Greene Tweed offers precision plastic components for a variety of demanding, semiconductor applications. These components are made from a full range of high-performance plastic materials, including Arlon® 1330. Ideal for applications requiring exceptional wear resistance and chemical compatibility, Arlon® 1330 provides good dimensional stability without the addition of carbon fibers.

Typical Properties		
Physical Properties	Typical	
Color	Tan	
Specific Gravity	1.38	
Melt Point (Pellet), °F (°C)	649 (343)	
Hardness, Shore D	85	
Water Absorption, 24 Hours, %	0.35	
Mechanical		
Tensile Break Strength, psi	12,600	
Elongation, %	20	
Flexural Strength, psi	21,100	
Flexural 0.5% Secant Modulus, psi	535,000	
Compressive Strength @ Break, psi	15,500	
Coefficient of Dynamic Friction PV=12,600 psi ft/min.	0.15	
Wear Factor, in.3-min./lb-ft-hr x 10-10	20	
Shear Strength @ Room Temperature		
Axial, psi	11,250	
Transverse, psi	Not Applicable	
Shear Strength @ 450°F (232°C)	·	
Axial, psi	2,870	
Transverse, psi	Not Applicable	
Izod Impact Strength		
Notched, ft-lb/inch	1.06	
Unnotched, ft-lb/inch	18.74	



Typical Properties (continued)		
Thermal	Typical	
Heat Distortion Temperature Under Load, @ 264 psi, °F (°C)	330 (166)	
Coefficient of Thermal Expansion, <300°F (149°C), inch/inch per °F x 10 <sup>-5</sup>	2.3	
Coefficient of Thermal Expansion, >300°F (149°C), inch/inch per °F x 10 <sup>-5</sup>	8.2	

#### **Features and Benefits**

- · Excellent chemical compatibility
- · Low extractables
- · Good dimensional stability
- Superior wear properties

#### **Applications**

- CMP retainer Rings
- Guides
- Supports

Contact Us

Greene Tweed Tel: +1.215.256.9521 Kulpsville, PA, USA Fax: +1.215.256.0189 Statements and recommendations in this publication are based on our experience and knowledge of typical applications of this product and shall not constitute a guarantee of performance nor modify or alter our standard warranty applicable to such products.

© 2018, Greene Tweed all rights reserved. All trademarks are property of their respective owners.

10/18-GT DS-US-SC-037