




# Fireproof Hydraulic Seal (FPH Seal™)

First to Market for the Aerospace, Defense, and Space Industries



FPH Seal™ Design:  
3D View, Patented Design

## Features and Benefits

- Sealing system passed fireproof testing (2000°F avg. for 15 minutes) for hydraulic sealing applications on aircraft
- Uses standard aerospace glands in accordance with AS4716 and AS5857\*
- Alternative to traditional fire shields that are typically heavy, bulky, easily damaged, costly, and require assembly

\*In most instances, two backup width glands are required. Open/two-piece glands provide easy installation.

## FPH Seal™ Innovation

Greene Tweed's Fireproof Hydraulic Seal (FPH Seal™) provides excellent high- and low-hydraulic pressure sealing in static applications for fireproof-rated equipment (1093°C/2000°F minimum average for 15 minutes).

Greene Tweed recognized the need for a new hydraulic seal design that would meet fireproof requirements, while providing static sealing capabilities in fire- and flame-resistant equipment, such as thrust reverser actuator systems (TRAS), fuel systems, and thrust vectoring/nozzle systems.



Static Sealing Applications



Greene Tweed Testing of FPH Seal™



Outside Laboratory Fire Test in Progress

## Greene Tweed and Outside Laboratory Fire Testing

Extensive testing was performed in Greene Tweed's in-house testing laboratory on multiple design variations. The resultant design was resistant to temperature elevations and able to retain fluid pressure.

The FPH Seal™ was then tested at an outside laboratory to verify performance under exact DO-160G and ISO 2685 test parameters, which included application of pressurized phosphate ester to the seal, a calibrated kerosene burner, and vibration.

During those tests, no pressure drops were experienced and the fixtures did not produce smoke that would be typical of a leaking unit. In addition, the fixtures held pressure well after the end of each test (10+ minutes beyond the 15-minute duration).

## Greene Tweed

1684 South Broad Street, Lansdale, PA 19446 USA | Phone: (+1) (215) 256-9521

[gtweed.com](http://gtweed.com)

Statements and recommendations in this publication are based on our experience and knowledge of typical applications of this product and shall not constitute a guarantee of performance nor modify or alter our standard warranty applicable to such products.

© 2026, Greene Tweed all rights reserved. All trademarks are property of their respective owners. 4/26-GT BR-US-MSE-26-001